

¡PROTEJA SUS EXPORTACIONES!



www.j2servid.com

LASHING TENSIONER WITH BATTERY J2300



POWERFUL & RELIABLE

Tensioning Force – Max. Tension 800 daN.

Industrial Grade Tool – This tensioner is completely designed and newly molded for Industrial Grade use.

The CA-SIG 32BT Power is NOT made by simply attaching a typical electric drill to a manual windlass tensioner.

SMART & EASY

Electronic Control Unit (ECU) – 3 pre-programmed tension modes: Auto/Semi/ Manual. And tension torque (1-6 levels) are electronically controlled (No need to hand turn a manual clutch to change torque).

Designated Quick Reverse Button (QRB) – preprogrammed auto reverse button allows for easy reverse turning of the windlass for quick tool removal after tension (without having to switch back and forth on the Forward/Reverse button on a typical electric drill).

Cutter – designed to cut Composite cord straps.

SPECIFICATION

Strap type: Composite & Woven cord strapping

Strap width: 19 - 32mm; Thickness: 0.85~1.65mm

Tensioning force: 6 settings (300 - 800 daN)

Tensioning speed: 35 mm/s

Weight including battery: approx. 3.6 kg

SAFETY

Single-handed operation **conforms to CE safety directive** and meets RoHS requirements.

Li-Ion battery **complies with UN38.3** safety requirements.

LATEST TECHNOLOGY

Brushless Motor – This 4th generation Brushless Motor generates a very steady output to ensure consistent and reliable tensioning for your cord strapping needs.

Bosch 18V 4.0Ah Li-Ion Battery – rechargeable battery with Charge Level Indicator (CLI), can strap up to 350 cycles per fully charged battery.

ERGONOMIC

6 Degree Angle on the handle bar – ergonomically designed to lessen wrist fatigue while tensioning on a flat surface, and during vertical operation.

Low Center of Gravity design – reduced the overall height of the tensioner to lessen operating fatigue during horizontal & vertical operation.